

PRODUCT BULLETIN

MKW DF-A

MKW DF-A is an all-purpose defoamer. It is based on 2-Ethyl Hexanol and modified fatty acid derivatives. It is a water dispersible premium grade defoamer.

Typical Physical Properties

Common Name	Defoamer	Chemical Formula	Proprietary Blend
Appearance	Clear Golden Straw Liquid	Solubility in Water @ 25 °C	Insoluble
Specific Gravity	0.850 - 0.925	Flash Point	> 100 °C

Application

MKW DF-A is used in any application where it is desirable to reduce the foaming tendencies of water base mud. It suppresses foam in all types of water-based mud including brines. It is compatible with all water base systems and restores pump pressure reduced by air or gas in the drilling mud.

Recommended Handling

All personnel handling this material must handle it as an industrial chemical, wearing protective equipment and observing the precautions as described in the Material Safety Data Sheet (MSDS).

Packaging and Storage

Packed in 55 USG Steel drum.

Store in dry, well-ventilated area. Keep container closed. Keep away from heat, sparks and flames. Store away from incompatibles. Follow safe warehousing practices regarding palletizing, banding, shrink-wrapping and /or stacking.

This document is supplied solely for informational purposes and Mykowell makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data. All product warranties and guarantees shall be governed by the Standard Terms of Sale.