



MKW DRILL LUBE R

MKW DRILL LUBE R is a water-dispersible lubricant.

Typical Physical Properties

Common Name	Drilling Lubricant	Chemical Formula	Proprietary Blend
Appearance	Dark Brown/Black Liquid	Solubility in Water @ 25 °C	Insoluble
Specific Gravity	0.95 - 1.00	Flash Point	> 115 °C

Application

MKW DRILL LUBE R is designed to decrease the coefficient of friction in all water-base muds, which lowers torque and drag in the wellbore. It contains no hydrocarbons and is compatible with all water-base fluids. It is completely water dispersible and blends easily into all mud systems.

Recommended Handling

All personnel handling this material must handle it as an industrial chemical, wearing protective equipment and observing the precautions as described in the Material Safety Data Sheet (MSDS).

Packaging and Storage

Packed in 55 USG HDPE drum or 1000 Litre IBC (Tote Tank).

Store in dry, well-ventilated area. Keep container closed. Keep away from heat, sparks and flames. Store away from incompatibles. Follow safe warehousing practices regarding palletizing, banding, shrink-wrapping and /or stacking.

This document is supplied solely for informational purposes and Mykowell makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data. All product warranties and guarantees shall be governed by the Standard Terms of Sale.



Mykowell Private Limited

Room 906, Xinjianye Building, No.303 Dongfeng East Street,
Kuiwen District, Weifang City, Shandong, China
Tel: (86) 536 8263216 | Fax: (86) 536 8291558 | info@mykowell.net